



Rack and pinion passenger/goods hoist

Without counterweight - single or twin operation (1 or 2 cages)

PEGA 2832 TD VFC

TECHNICAL DATA

CAPACITY PER CAGE

Payload capacity	2800 kg
Passengers	24
Erection load	1000 kg
Speed	0-100 m/min
Rated lifting height	0-420 m
Maximum tie spacing	12 m

DIMENSIONS PER CAGE

Internal width x length	1,5 x 3,2 m
Internal minimum height	2,49 m
Door opening w x h	1,43 x 2,0 m
Mast section length	1,508 m

ELECTRICAL DATA PER CAGE

Power supply	380-460V 3Ph 50/60 Hz
Power supply fuses	63-125 A
Rated power	37-75 kW
Starting current	66-131 A
Running current (40% duty)	51-101 A
Power consumption	38-70 kVA

WEIGHTS PER CAGE

Base unit and enclosure	3400 kg
Cage weight	2400 kg
Mast section with 2 racks	175-215 kg

CONTROL SYSTEM

Joystick/ Push button/ Key pad control
Preprogrammable floor stops
Other control systems on request

Generall:

All lifts equipped with frequency controlled drives
and programmable control systems


Cable basket or cable trolley operation

Variety of opional equipment

Different masts and tie- systems to meet all kind of application demands

Doors installations in different positions and combinations

The above specification may vary based on country and region of delivery.



CONSULT - RENT - SALE - SERVICE

PEGA HOIST Ltd.

Fablovka 547
CZ - 533 52 Pardubice
Tel. : +420 466 536 348, 466 536 350
Fax : +420 466 536 351
E-mail : info@pega-hoist.com
www.pega-hoist.com

Local representative

The technical data above are for information only. The manufacturer reserves the right to change the parameters subject to continuous development and improvements.